## **Environmental Protection Agency**

Reference	Applies to sub-	Comment
63.7(a)-(d)		If an alternative means of limiting emissions (e.q., an add-on control system) is used to
05.7(a)–(u)	140	comply with subpart II in accordance with §63.783(c), then these sections do apply.
63.7(e)(1)	No	If an alternative means of limiting emissions (e.g., an add-on control system) is used to comply with subpart II in accordance with §63.783(c), then see §63.786(e).
63.7(e)(2)-(e)(4)	No	If an alternative means of limiting emissions (e.g., an add-on control system) is used to comply with subpart II in accordance with §63.783(c), then these sections do apply.
63.8	No	If an alternative means of limiting emissions (e.g., an add-on control system) is used to comply with subpart II in accordance with §63.783(c), then this section does apply, with the exception of §63.8(c)(1)(i), §63.8(c)(1)(iii), and the last sentence of §63.8(d)(3).
63.9(a)-(d)	Yes	\$63.787(a) extends the initial notification deadline to 180 days. §63.787(b) requires an implementation plan to be submitted with the initial notification.
63.9(e)	No	If an alternative means of limiting emissions (e.g., an add-on control system) is used to comply with subpart II in accordance with §63.783(c), then this paragraph does apply.
63.9(f)	No	Subpart II does not contain any opacity or visible emission standards
63.9(g)–(h)		If an alternative means of limiting emissions (e.g., an add-on control system) is used to comply with subpart II in accordance with §63.783(c) then these paragraphs do apply.
63.9(i)-(j)	Yes.	
63.10(a)	Yes.	
63.10(b)(1)	Yes.	
63.10(b)(2)(i)	No.	
63.10(b)(2)(ii)	No	See §63.788(b)(5) for recordkeeping of occurrence, duration, and actions taken during mal- functions.
63.10(b)(2)(iii)	Yes.	
63.10(b)(2)(iv)– (b)(2)(v).	No.	
63.10(b)(2)(vi)– (b)(2)(xiv).	Yes.	
63.10(b)(3)	Yes.	
63.10(c)(1)–(9)	No	If an alternative means of limiting emissions (e.g., an add-on control system) is used to comply with subpart II in accordance with §63.783(c), then these sections do apply.
63.10(c)(10)- (11).	No	If an alternative means of limiting emissions (e.g., an add-on control system) is used to comply with subpart II in accordance with § 63.783(c), then see § 63.788(b)(5) for records of malfunctions.
63.10(c)(12)- (14).	No	If an alternative means of limiting emissions (e.g., an add-on control system) is used to comply with subpart II in accordance with §63.783(c), then these sections do apply.
63.10(c)(15)	No.	
63.10(d)(1)–(4)	Yes.	
63.10(d)(5)	No	See § 63.788(c) for reporting malfunctions.
63.10(e)	No	If an alternative means of limiting emissions (e.g., an add-on control system) is used to comply with subpart II in accordance with §63.783(c), then this paragraph does apply.
63.10(f)	Yes.	0017 00(0), then the paragraph does apply.
63.11	No	If an alternative means of limiting emissions (e.g., an add-on control system) is used to comply with subpart II in accordance with §63.783(c), then this section does apply.
63.12–63.15	Yes.	comply with subpart if in accordance with \$00.700(c), then this section does apply.

[60 FR 64336, Dec. 15, 1995, as amended at 76 FR 72070, Nov. 21, 2011]

Table 2 to Subpart II of Part 63—Volatile Organic HAP (VOHAP) Limits for Marine Coatings

	VOHAP limits a,b,c				
Coating category	Grams/liter coating (minus water and exempt	Grams/liter solids <sup>d</sup>			
	compounds)	t ≥4.5 °C	t <4.5 °C e		
General use	340	571	728		
Specialty:					
Air flask	340	571	728		
Antenna	530	1,439			
Antifoulant	400	765	971		
Heat resistant	420	841	1,069		
High-gloss	420	841	1,069		
High-temperature	500	1,237	1,597		
Inorganic zinc high-build	340	571	728		
Military exterior	340	571	728		
Mist	610	2,235			
Navigational aids	550	1,597			
Nonskid	340	571	728		
Nuclear	420	841	1,069		

	VOHAP limits a,b,c				
Coating category		Grams/liter solids <sup>d</sup>			
	exempt compounds)	t ≥4.5 °C	t <4.5 °C e		
Organic zinc	360	630	802		
Pretreatment wash primer	780	11,095			
Repair and maint. of thermoplastics	550	1,597			
Rubber camouflage	340	571	728		
Sealant for thermal spray aluminum	610	2,235			
Special marking	490	1,178			
Specialty interior	340	571	728		
Tack coat	610	2,235			
Undersea weapons systems	340	571	728		
Weld-through precon. primer	650	2.885			

a The limits are expressed in two sets of equivalent units. Either set of limits may be used for the compliance procedure described in §63.785(c)(1), but only the limits expressed in units of g/L solids (nonvolatiles) shall be used for the compliance procedures described §63.785(c) (2) through (4).

b VOC (including exempt compounds listed as HAP) shall be used as a surrogate for VOHAP for those compliance procedures described in §63.785(c) (1) through (3).

c To convert from g/L to lb/gal, multiply by (3.785 L/gal)(1/453.6 lb/g) or 1/120. For compliance purposes, metric units define the standards

[60 FR 64336, Dec. 15, 1995, as amended at 61 FR 66228, Dec. 17, 1996; 76 FR 72070, Nov. 21, 2011]

TABLE 3 TO SUBPART II OF PART 63—SUMMARY OF RECORDKEEPING AND REPORTING REQUIREMENTS  $^{\mathrm{ABC}}$ 

Tungoniani	10								
Requirement		All Opts.		Option 1		Option 2		Option 3	
		Rep	Rec	Rep	Rec	Rep	Rec	Rep	
Notification (§ 63.9(a)—(d)) Implementation plan (§ 63.787(b)) d Volume of coating applied at unaffected major sources (§ 63.781(b)) Volume of each low-usage-exempt coating applied at affected sources (§ 63.781(c)) ID of the coatings used, their appropriate coating categories, and the applicable VOHAP limit  Determination of whether containers meet the standards described in § 63.783(b)(3)  Results of M—24 or other approved tests Certification of the as-supplied VOC content of each batch Certification of the as-applied VOC content of each batch Maximum allowable thinning ratio(s) for each batch Maximum allowable thinning ratio(s) for each batch Total allowable volume of thinner Actual volume of thinner used Identification of each group of coatings and designated thinners	X X X X X	X X X X	××	x	X X X X	X X X X	× × × ×	X X X X	

or 10 convert from g/L to lorgal, multiply by (3.785 L/gal)(1/453.6 lb/g) or 1/120. For compliance purposes, metric units define the standards.

dVOHAP limits expressed in units of mass of VOHAP per volume of solids were derived from the VOHAP limits expressed in units of mass of VOHAP per volume of coating assuming the coatings contain no water or exempt compounds and that the volumes of all components within a coating are additive.

derivatively the standard per limits apply during cold-weather time periods, as defined in §63.782. Cold-weather allowances are not given to coatings in categories that permit less than 40 percent volume solids (nonvolatiles). Such coatings are subject to the same limits regardless of weather conditions.

a Affected sources that comply with the cold-weather limits must record and report additional information, as specified in § 63.788(b)(3) (ii)(C), (iii)(C), and (iv)(D).

b Affected sources that detect a violation must record and report additional information, as specified in § 63.788(b)(4).

c OPTION 4: the recordkeeping and reporting requirements of Option 4 are identical to those of Options 1, 2, or 3, depending on whether and how thinners are used. However, when using Option 4, the term "VOHAP" shall be used in lieu of the term "VOC," and the owner or operator shall record and report the Administrator-approved VOHAP test method or certification procedure.

dure.

dure.

dures a Major sources that intend to become area sources by the compliance date may, in lieu of submitting an implementation plan, choose to submit a statement of intent as specified in §63.787(b)(4).